

規格表(Product Datasheet)

Nitta Japan 型號	表面材質	表面顏色	抗拉層材質	滾輪面材質	滾輪面顏色	永久抗靜電	總厚度 (mm)	延伸1% 拉力(N/mm)	最大容許 拉力(N/mm)	最小輪徑 限制(mm)	工作溫度 (°C)
SG-250	NBR	Green	PA	NBR	Black	●	0.8	3.0	60	25	-20~+80
SG-350	NBR	Green	PA	NBR	Black	●	0.9	5.3	105	35	-20~+80
SG-500	NBR	Green	PA	NBR	Black	●	1.1	7.5	150	50	-20~+80
SG-750	NBR	Green	PA	NBR	Black	●	1.3	11.3	225	75	-20~+80
SG-1000	NBR	Green	PA	NBR	Black	●	1.6	15.0	300	100	-20~+80
L-250	NBR	Blue	PA	NBR	Black	●	1.4	3.0	60	25	-20~+80
L-350	NBR	Blue	PA	NBR	Black	●	1.5	5.3	105	35	-20~+80
L-500	NBR	Blue	PA	NBR	Black	●	1.6	7.5	150	50	-20~+80
L-750	NBR	Blue	PA	NBR	Black	●	2.2	11.3	225	75	-20~+80
L-1000	NBR	Blue	PA	NBR	Black	●	2.5	15.0	300	100	-20~+80
L-1500	NBR	Blue	PA	NBR	Black	●	3.1	22.5	450	150	-20~+80
L-2000	NBR	Blue	PA	NBR	Black	●	3.6	30.0	600	200	-20~+80
M-250	NBR	Blue	PA	NBR	Black	●	2.2	3.0	60	30	-20~+80
M-350	NBR	Blue	PA	NBR	Black	●	2.4	5.3	105	40	-20~+80
M-500	NBR	Blue	PA	NBR	Black	●	2.5	7.5	150	50	-20~+80
M-750	NBR	Blue	PA	NBR	Black	●	2.8	11.3	225	75	-20~+80
M-1000	NBR	Blue	PA	NBR	Black	●	3.0	15.0	300	100	-20~+80
M-1500	NBR	Blue	PA	NBR	Black	●	3.5	22.5	450	150	-20~+80
M-2000	NBR	Blue	PA	NBR	Black	●	4.0	30.0	600	200	-20~+80
H-500	NBR	Blue	PA	NBR	Black	●	3.5	7.5	150	60	-20~+80
H-750	NBR	Blue	PA	NBR	Black	●	3.7	11.3	225	75	-20~+80
H-1000	NBR	Blue	PA	NBR	Black	●	4.0	30.0	300	100	-20~+80
H-1500	NBR	Blue	PA	NBR	Black	●	4.5	22.5	450	150	-20~+80
H-2000	NBR	Blue	PA	NBR	Black	●	5.0	30.0	600	200	-20~+80
XH-500-3	NBR	Blue	PA	NBR	Blue	●	3.0	3.8	150	50	-20~+80
XH-500-3.5	NBR	Blue	PA	NBR	Blue	●	3.5	3.8	150	55	-20~+80
XH-500-4	NBR	Blue	PA	NBR	Blue	●	4.0	3.8	150	60	-20~+80
XH-500-5	NBR	Blue	PA	NBR	Blue	●	5.0	3.8	150	70	-20~+80
XH-500-6	NBR	Blue	PA	NBR	Blue	●	6.0	3.8	150	80	-20~+80
RT-300	NBR	Blue	PE	PET	Black	●	7.0	3.0	290	100	-20~+80
RT-500	NBR	Blue	PE	PET	Black	●	7.0	3.8	150	90	-20~+80
KSG-250	NBR	Green	PA	Fabric	Black	●	0.9	3.0	60	20	0~+80
KSG-350	NBR	Green	PA	Fabric	Black	●	1.0	10.5	105	35	0~+80
TFL-6S	NBR	Blue	PA	NBR	Grey	●	2.25	23	230	40	-20~+80
TFL-7S	NBR	Blue	PA	NBR	Grey	●	2.4	30	300	50	-20~+80
TFL-10S	NBR	Blue	PA	NBR	Grey	●	2.6	39	390	70	-20~+80
TFL-15S	NBR	Blue	PA	NBR	Grey	●	3.1	60	600	110	-20~+80
TFL-18S	NBR	Blue	PA	NBR	Grey	●	3.35	68	680	130	-20~+80
TFL-15E20	NBR	Blue	TPU	NBR	Black	●	2	15	150	40	0~+60
TFL-22E26-2	NBR	Blue	TPU	NBR	Black	●	2.6	22	180	50	0~+60
TLA-30E30-2	NBR	Blue	TPU	NBR	Black	●	3	30	250	70	0~+60
FZ-5E12	NBR	Green	TPU	NBR	Green	●	1.25	5	90	35	-20~+60
LA-4E14	NBR	Blue	TPU	NBR	Blue	●	1.4	8	45	25	-20~+60
SLA-8E14	NBR	Blue	TPU	NBR	Blue	●	1.4	8	90	25	-20~+60
DB-4E14	TPU	Blue	PES	TPU	Blue	●	1.4	4	-	25	-20~+60
NTD	PES	Blue	TPU	TPU	Black	●	1.35	1	-	25	-20~+60
TA-09	TPU	Blue	TPU	TPU	Black	●	0.9	0.5	-	20	-20~+60
TA-12	TPU	Blue	TPU	TPU	Black	●	1.2	0.7	-	25	-20~+60

Nitta Holland 型號	輸送面 顏色	輸送面 材質	食品認證	HACCP認證	摩擦力	永久抗靜電	總厚度 (mm)	延伸1% 拉力(N/mm)	最大容許 拉力(N/mm)	最小輪徑 限制(mm)	工作溫度 (°C)
1 LRAFP 02/G2 M 0,7	D. G.	TPU	v	-	MF	●	0.7	4.0	6.0	8	-20~+80
2 LRAFP 02/G2 IM M 1.4	D. G.	TPU	v	-	MF	●	1.4	9.0	12.0	10	-20~+80
2 XRAFP 03/PG IM M	Petrol	TPU	v	-	LF	●	2.2	9.0	16.0	40	-10~+80
1 LRAFP 02/W2 IM M	White	TPU	v	-	MF	-	0.7	4.0	6.0	8	-20~+80
1 LRAFP 02/W2 M	White	TPU	v	-	LF	●	0.8	4.0	6.0	10	-10~+80
2 LRAFP IM 0.9	White	IMPREG.	v	-	LF	●	0.9	8.0	12.0	10	-10~+80
2ULRAFP 02/W2 IM M1.4	White	TPU	v	-	LF	●	1.4	8.0	12.0	8	-20~+80
2 LRF	White	Fabric	v	-	LF	-	1.6	8.0	17.0	20	-10~+90
2 LRAF 901/901	Black	IMPREG.	-	-	LF	●	1.6	8.0	17.0	30	-10~+90
2 LRWAF 905 M FR3	Black	PVC	-	-	LF	●	2.1	10.0	18.0	40	-10~+80
2 NF 906 FR3-IM	Black	PVC	-	-	HF	●	2.4	12.0	22.0	50	-10~+80
2 LRWAF 909 RB FR3	Black	PVC	-	-	HF	●	2.95	10.0	18.0	40	-10~+80
2 LRAWF 1310GP	Petrol	PVC	-	-	HF	-	2.8	10.0	18.0	40	-10~+80
2 LRF 272 RT 55	Green	PVC	-	-	HF	-	6.0	8.0	17.0	50	-10~+80
2 LRAF-HY 02	Transp.	Hytrel	v(Dry)	-	HF	●	1.7	9.0	12.0	15	-10~+110